

FUEL INJECTOR

FIELD OF THE INVENTION

The present invention relates to a fuel injector.

BACKGROUND INFORMATION

5 During operation of an engine, a problem generally occurs in
the case of direct injection of a fuel into the combustion
chamber of an internal combustion engine, particularly in the
case of direct gasoline injection or the injection of diesel
fuel, that the downstream tip of the injection valve
10 projecting into the combustion chamber is coked by fuel
deposits or that soot particles formed in the flame front are
deposited on the valve tip. Therefore, in the conventional
arrangement of injection valves projecting into the combustion
chamber, there is the danger during its lifetime of a negative
15 influence on the spray parameter (e.g., static flow quantity,
spray angle, drop size, skeining) that can lead to operational
disturbances of the internal combustion engine or to a
malfunction of the injection valve.

SUMMARY

20 The injector valve according to the present invention may
provide that the negative effects of coking (soot depositing),
e.g., on the valve tip projecting into the combustion chamber
including its outlet openings, may be restricted or
25 eliminated. Forming a device for accumulating
combustion-chamber gas with access to the dead volume arranged
between valve needle end and the spray region including the
outlet openings in accordance with the present invention makes
it possible to largely prevent coke deposits in the outlet
30 openings. The buoyancy of the gas phase with respect to the
liquid phase causes the gas to remain in the device for
accumulating combustion chamber gas.

In this manner, the spray parameter and the valve function are able to be maintained in a stable manner during its entire lifetime even in the case of direct injection of fuel into a combustion chamber at the fuel injection valves.

5

One or more blind holes may be provided on the valve needle end facing the outlet openings, i.e., on the surface of the valve-closure member facing the dead volume. In this context, it may be ensured that the blind holes have access to the dead volume and that the gas volume is not able to escape from the gas accumulation volume by buoyancy force.

10

15

An example embodiment of the present invention is represented in simplified form in the drawing, and is explained in detail in the following description.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a cross-sectional view of a part of a fuel injector.

20

Figure 2 is a schematic cross-sectional view of an outlet opening having a breaking-off liquid column arranged therein.

DETAILED DESCRIPTION

25

Figure 1 partially illustrates a valve in the form of an injection valve for fuel injection systems of mixture-compressing, externally ignited internal combustion engines as an example embodiment. The injection valve has a tubular valve-seat support 1, in which a longitudinal opening 3 is formed concentrically to a longitudinal valve axis 2. Arranged in longitudinal opening 3 is a, for example, tubular valve needle 5, which is securely connected at a downstream end 6 to a, for example, spherical valve closure member 7, on the periphery of which, for example, five flattenings 8 are provided for the fuel to flow past.

30

35

Express Mail No. 244511405

The fuel injector is actuated in a conventional manner, e.g., electromagnetically. A schematically indicated electromagnetic circuit having magnetic coil 10, an armature 11, and an core 12 is used for axially moving valve needle 5, and as such, for opening the fuel injector against the spring force of a restoring spring and for closing the fuel injector. Armature 11 is connected, for example, by a welded seam formed by a laser to the end of valve needle 5 away from valve-closure member 7, and is aligned with core 12.

A guide opening 15 of a valve-seat member 16, which is sealingly mounted by welding in the downstream end of valve-seat support 1 away from core 12, in longitudinal opening 3, which extends concentrically to longitudinal valve axis 2, is used for guiding valve-closure member 7 during the axial movement. Valve-seat member 16 has a cupped configuration, for example, a jacket part 17 of valve-seat member 16 transitioning in the direction of armature 11 into a collar 18 abutting against valve-seat support 1. On the side opposite collar 18, valve-seat member 16 has a base part 19, which is convexly curved, for example.

The insertion depth of valve-seat member 16 determines the magnitude of the lift of valve needle 5 since the one end position of valve needle 5 in the case of a non-energized magnetic coil 10 is determined by the seating of valve-closure member 7 at valve-seat surface 22, which tapers conically in a downstream direction or has a slightly curved configuration, on base part 19 of valve-seat member 16. Given an energized magnetic coil 10, the other end position of valve needle 5 is determined, e.g., by the seating of armature 11 on core 12. The path between these two end positions of valve needle 5 represents the lift. Spherical valve-closure member 7 cooperates with truncated-cone-shaped or curved valve-seat surface 22 of valve-seat member 16, which is formed between guide opening 15 and a plurality of outlet openings 23 inserted in a central region of base part 19 of valve-seat

member 16. Base part 19 forms the spray-discharge region of the fuel injector.

In particular, the fuel injector is configured as a so-called multi-hole valve that is particularly suited for injecting fuel directly into a combustion chamber. In this context, at least two or also four or significantly more outlet openings 23 are inserted in base part 19 of valve-seat member 16, e.g., via erosive machining, laser drilling, punching, etc. For a desired filling of the combustion chamber with fuel, outlet openings 23 are aligned, for example, at different angles to longitudinal valve axis 2, all outlet openings 23, for example, moving away from longitudinal valve axis 2 in the downstream direction at an angle.

Especially such multi-hole valves for directly injecting fuel into a combustion chamber the outlet openings of which are directly subjected to the combustion chamber atmosphere are extremely susceptible to coking. Such outlet openings may have build-up on their periphery due to coke deposits, thereby making it impossible for the desired injection quantities to be dosed and metered in acceptable amounts.

The fuel injector according to the present invention may largely prevent coke deposits of the combustion chamber in the region of outlet openings 23 from obstructing the outlet openings and significantly changing the injection quantities during the valve's lifetime.

Since valve-closure member 7 and curved base part 19 of valve-seat member 16 are formed with different radii, there is, when the injector valve is closed, an enclosed space representing a dead volume 25 within annular valve-seat surface 22 in the region of outlet openings 23, between valve-closure member 7 and base part 19. In accordance with the present invention, gas is to be accumulated in dead volume 25 in order to prevent coke deposits at outlet openings 23.

Before this functional principle of gas accumulation is described, the creation of coke deposits is to be briefly explained.

5 The processes of through-flow and coking are subsequently explained with reference to Figure 2, which schematically illustrates an outlet opening 23. When valve-closure member 7 is pressed back at the end of the injection operation onto valve-seat surface 22, the flow through outlet openings 23 is
10 stopped abruptly. Therefore, no more fuel continues to flow through the sealing seat region past valve-seat surface 22 into dead volume 25.

15 Due to its weight, liquid column 27, which is emerging from outlet openings 23 immediately prior to the closing of the valve, possesses a certain inertia. The low pressure in liquid column 27 produced as a result of the closing of the valve and of the associated stop of the flow in the sealing seat region becomes greater as a function of inertia starting from an
20 outlet plane 28 of outlet opening 23 in the downstream direction within outlet opening 23. At a certain location 29 within liquid column 27, the vapor pressure of the liquid is insufficient. A vapor phase forms suddenly at this location 29, thereby causing part 30 of liquid column 27, which is
25 downstream of this location 29, to break away from the remaining liquid as a result of inertia.

A meniscus of liquid at which there is a phase boundary between the liquid and the gas surrounding the valve forms
30 within outlet opening 23. When injecting fuel directly into a combustion chamber, all components directly on the combustion chamber, therefore also a direct injection valve, in particular outlet openings 23, which project into the combustion chamber, are subjected to an extreme influence of
35 heat. During combustion, coke residues may form on the above-mentioned phase boundary in particular and build-up on the wall of outlet opening 23, thereby resulting in the

previously explained disadvantages. Consequently, in the case of conventional valves, annular coke deposits that disadvantageously constrict flow result at a certain depth in outlet openings 23.

5

In the configuration of the fuel injector according to the present invention, outlet openings 23 are completely emptied for which reason no coke deposits are able to form within outlet openings 23. In accordance with the present invention, a device for gas accumulation is, therefore, produced directly at dead volume 25. In the example embodiment illustrated in Figure 1, this device for gas accumulation is configured as central blind hole 33 in valve-closure member 7 on its surface facing dead volume 25. Blind hole 33 is filled with combustion chamber gas, i.e., with the air dissolved in the fuel. The buoyancy of the gas phase with respect to the liquid phase causes the gas to remain in blind hole 33.

When opening the valve by raising valve-closure member 7 from valve-seat surface 22, the fluid pressure in dead volume 25 increases, thereby compressing the gas volume in blind hole 33. In this context, the gas is pressed further into blind hole 33. When closing the valve, the fluid pressure decreases again, and the gas volume expands again within blind hole 33. Since additional fluid is prevented from flowing into dead volume 25 when the valve is closed, an underpressure is produced in the liquid phase as a result of the inertia of the just emerged fluid. As a result, the gas volume of blind hole 33 is able to expand even further, so that it partially reaches into dead volume 25. The fluid volume expelled in this manner is able to flow out of outlet opening 23.

While a pressure equilibrium returns in dead volume 25, the remaining fluid volume recedes from outlet openings 23 into dead volume 25 as a result of a contraction of the gas phase. Outlet openings 23 fill completely with combustion chamber gas. The liquid column disappears completely from outlet

openings 23. In this manner, there is also no more meniscus of liquid column 27 in outlet opening 23 for which reason disadvantageous, annular coking deposits are also not able to form in outlet opening 23.

5

Instead of an individual blind hole 33, a plurality of smaller blind holes 33 may also be provided next to one another on the valve needle end facing outlet openings 23, i.e., on valve-closure member 7. This arrangement may provide the advantage that given the same gas accumulation volume, the cross section of individual blind holes 33 is smaller and, consequently, the capillary effect in blind holes 33 increases. Therefore, the accumulated gas is even less able to be expelled by flow forces of the liquid.

10

15

The valve needle tip, i.e., valve-closure member 7 is not the only component part of the fuel injector on which blind holes of the present invention are able to be formed. Rather, it may be ensured that blind holes 33 have access to dead volume 25 and that the gas volume is not able to escape from the gas accumulation volume by buoyancy force.

20